



TECHNICAL DATASHEET

TRADE NAME	:	MFCARB WT C50200
APPLICATION	:	Water TREATMENT
SOURCE	:	COCONUT
ACTIVATION AGENT	:	STEAM/AIR
MESH SIZE	:	50X200 USS MESH

PARAMETER	UNIT	SPEC.	TEST METHOD
Apparent density	Kg/m ³	380 min.	ASTM D2854
Ash Content	Wt. %	5 max.	ASTM D2866
Iodine Number	mg/gm	1000	ASTM D4067
Moisture	Wt. %	5 max.	ASTM D2867
pH	-	9-11	ASTM D3838
Hardness	%	98	ASTM D3802
Surface Area	m ² /gm	1025 min.	BET-m ²

+50USS MESH	Wt. %	5 max.	ASTM D2862
-200 USS MESH	Wt. %	5 max.	ASTM D2862

PACKING The material is packaged in 500kgs/550 Kgs net in poly woven bags or 25kgs net in PP bags with inner lining will be shrink wrapped and palletized in to fumigated Pallets as per ISPM 15 standard.

STORAGE: Store the material in a cool dry area, away from sunlight. **SHELF LIFE:** More than 5 Years when keeping in proper packed condition

LABELING: The label displays the product name, lot number, net weight, gross weight, manufacturer name & address and other information or marks as required by the customer

