

# GFPES-Series Food and Beverage Grade Polyethersulfone


GFPES-Series High Purity Food and Beverage Grade Polyethersulfone Filter Cartridges meet the most demanding requirement of the food and beverage industry. The polyethersulfone membrane offers high flux density and low protein-binding and maintains the organoleptic characteristics of the treated product, making it an ideal choice for production of consumables. Cartridges are flushed with ultra-High Purity water to achieve the most stringent requirements for extractable substances. Designed to tolerate repeated hot water sanitization and in-situ steam sterilization cycles for maximum service life. Each element is diffusion tested for integrity to assure optimal performance. Manufactured in a clean-room environment to maintain high standards of purity and cleanliness.

### **Microbial Retention Performance**

Rating	Challenge Microbe	Log Reduction Value (LRV)		
0.2μ	Brevundimonas diminuta	7.6		
0.45μ	Serratia marcescens	6.6		
0.65µ	Saccharomyces cerevisiae	4.8		

<sup>\*</sup> Independently tested in accordance with ASTM F838.

# Flow Rate vs Pressure Drop





#### **Construction Materials**

Membrane	Polyethersulfone
Support Media	Polypropylene
End Caps	Polypropylene
Center Core	Polypropylene
Outer Support Cage	Polypropylene
O-Rings/Gaskets	Buna, EPDM, Silicone,
Teflon® Enca	apsulated Viton®, Viton®,
Teflor	n® Encapsulated Silicone

## Sanitization/Sterilization

Filtered Hot Water	80°C for 30 min
Steam Sterilization	121°C for 30 min.
	multiple cycles

**Chemicals:** Cartridges are compatible with most chemical sanitizing agents.

**Note:** Stainless steel insert option required for all cartridges being hot water sanitized or steam sterilized.

### **Typical Applications**

- Wine
- Beer
- Juices
- Soft Drinks
- Bottled Water

#### **Dimensions**

#### Length:

10 to 40 inches (25.4 to 101.6 cm) nominal

#### **Outside Diameter:**

2.70 inches (7.0 cm) nominal

### **Operating Conditions**

Change Out $\Delta P$ (recommen	ided35 PSIL
Temperature (max)	176°F (80°C)
Differential Pressure (max)	50 PSIC
	(3.4 bar) at 68°F (20°C)

## **Toxicity**

All polypropylene components meet the specifications for biological safety per USP Class VI – 121°C for plastics.

### **Food Safety Compliance**

Materials of construction comply with FDA regulations for food and beverage contact use as detailed in the US Code of Federal Regulations, 21CFR. Materials used to produce filter media and hardware are deemed safe for use in contact with foodstuffs in accordance with EU Directives 2002/72/EC, 1935/2004, and/or 10/2011.

### **Ordering Information**

GFPES	Rating (μ)	Α	Length	С	End Cap Style	O-Rings/Gaskets	Adders
	0.04		10" (25.4 cm)		2 = DOE Flat Gasket	B = Buna	CS = 316SS Compression Spring
	0.1		20" (50.8 cm)		3 = 222 w/ Fin	E = EPDM	I = Stainless Steel Insert
	0.2		30" (76.2 cm)		4 = 222 w/ Flat Cap	S = Silicone	
	0.45		40" (101.6 cm)		6 = 226 w/ Flat Cap	T = Teflon® Encapsulated Viton®	
	0.65				7 = 226 w/ Fin	V = Viton®	
	0.8				16 = 213 Internal O-Ring	Z = Teflon® Encapsulated Silicone	
					28 = 222 3-tabs w/ Fin		

DISCLAIMER: Filtration data presented is representative of performance observed in controlled laboratory testing. It is not given as a warranty, specification or statement of fitness for use. Specific performance can vary widely depending on contaminant type, fluid properties, flow rates and environmental conditions. It is recommended that users conduct thorough qualification testing to assure the product functions as required. For additional technical support, a product Performance Guide is available upon request.

DS GFPES 190918

