



## TECHNICAL DATA

## VIKING AFFF 3%S C6 FOAM CONCENTRATE

### 1. GENERAL DESCRIPTION

Viking AFFF 3%S C6 is an aqueous film forming foam concentrate (AFFF) consisting of fluorocarbon and hydrocarbon surfactants blended with various solvents, preservatives and stabilizers.

The foam forms an aqueous film that rapidly cuts off the oxygen supply and knocks down the fire. The expanded foam, from which the film is drained, forms a stable blanket that suppresses the release of flammable vapors and cools down the fuel surface extinguishing the fire and preventing reignition. The low surface tension of the water-foam solution enables the aqueous film, although heavier than the burning vapors, to float on top of the liquid surface.

Viking AFFF 3%S C6 should be used at 3% of the solution volume (3 parts concentrate in 97 parts of water) in brackish, fresh or sea water. It may also be stored as a premix solution in fresh water.

#### Features:

- Tested, Listed and Approved with Sprinklers.
- Excellent firefighting on Class A and Class B hydrocarbon fires
- For use in high risk applications such as warehouses, aircraft hangars, offshore installations, oil and chemical tankers, petrochemical and chemical plants.



### 2. LISTINGS AND APPROVALS



#### FM Approved

Refer to the FM Approval guide for systems and devices that are approved for use with this concentrate. Refer to the system and device data sheets from Viking, NFPA 11, FM Global Property Loss Prevention Data Sheets, and relevant local standards for correct system design. FM Approval of the foam extinguishing system is contingent upon the design, installation, testing and maintenance performed in accordance with NFPA 11 and/or FM Global Property Loss Prevention Data Sheet 4-12, Foam/Water Sprinkler Systems.



#### UL Listed - GFGV.EX27255

Underwriters Laboratories, UL 162 7th Edition Refer to the UL Listing for systems and devices that are approved for use with this concentrate. Refer to the system and device data sheets from Viking, NFPA 11, and relevant local standards for correct system design.

### 3. TECHNICAL DATA

#### Physical Data

Appearance .....	Clear to yellowish liquid
Specific gravity at 68 °F (20 °C).....	1,02 +/- 0.01 g/ml
Viscosity at 77 °F (25 °C) spindle #2, 60 rpm.....	5,5 mPas +/- 2
Viscosity at 68 °F (20 °C) spindle #2, 60 rpm.....	6 mPas +/- 2
Viscosity at 36 °F (2 °C) spindle #2, 60 rpm.....	8 mPas +/- 2
pH .....	6,5 to 8,5
Freezing point.....	27 °F (-3 °C)
Recommended storage temperature.....	27 to 131 °F (-3 to 55°C)
UL/FM temperature range .....	35 to 120 °F (1,7 to 49 °C)
Suspended sediment (v/v).....	Less than 0,2%
Surface tension .....	≤ 18,0 dynes/cm



## TECHNICAL DATA

## VIKING AFFF 3%S C6 FOAM CONCENTRATE

**TABLE 1: ORDERING INFORMATION**

Volume	Packaging	Part Number	Approximate Shipping Weight*		Dimensions* In (mm)		Sales Region
			Lbs.	Kg	Inches	mm	
25 Litres	Can	V-AFFF3S/25	55**	25**	11x10x17	295x260x441	EMEA/APAC
200 Litres	Drum	V-AFFF3S/200	461**	209**	23x23x37	581x581x935	EMEA/APAC
1000 Litres	IBC Tote	V-AFFF3S/1000	2340	1060	47x39x45	1200x1000x1150	EMEA/APAC
6.5 US Gallons	Can	F20336-6.5	27**	60**	11x10x29	295x260x737	AMERICAS
55 US Gallons	Drum	F20336-55	488**	221**	23x23x37	581x581x935	AMERICAS
265 US Gallons	IBC Tote	F20336-265	2393	1084	47x39x45	1200x1000x1150	AMERICAS
Bulk	Bulk tanker deliveries available by special request. Contact Viking for availability.						

\*Shipping Weight and Dimensions are approximate. \*\*Weight does not include pallet.

#### 4. ENVIRONMENTAL IMPACT

Viking AFFF 3%S C6 is formulated using specially selected raw materials, selected for their fire performance and their environmental profile. Viking AFFF 3%S C6 is biodegradable. It contains only C6 fluorotemomers. The handling of foam concentrate or foam solution spills should be in accordance with local regulations. Sewage systems should have no processing issues with a 3% foam solution based on Viking AFFF 3%S C6, but local sewage operators should be consulted in this respect. Our C6 foams contain no PFOA and no PFOS, in accordance with US EPA Stewardship Program 2010/15 and EU Directive 2006/122/EC and amended Council Directive 76/769/EEC. Full details will be found in the Safety Datasheet (SDS).

#### 5. APPLICATION

Viking AFFF 3%S C6 is intended for use on Class A and Class B hydrocarbon fuel fires such as oil, diesel and aviation fuels as well as Class A fires such as wood, paper, textiles etc. Refer to the FM Approval Guide and UL Listing for approved fuel hazards and application rates. It can be used with both aspirating and non-aspirating discharge devices. Viking AFFF 3%S C6 is especially suited whenever rapid fire knock-down is essential. It is compatible with all dry chemical powders and can be used in powder/foam twin agent systems; however, this statement is not verified by UL or FM.

#### 6. PROPORTIONING

Viking AFFF 3%S C6 can easily be proportioned at the correct dilution using conventional equipment such as:

- Inline inductors
- Inline Balanced Pressure, proportioning systems (ILBP)
- Bladder tanks and ratio controllers
- Around the pump proportioning systems
- Water motor or turbine foam proportioners
- Self inducting branch pipes and nozzles

Refer to the FM Approval Guide and UL Listing for proportioning equipment approved for use with this concentrate.

#### 7. FIRE PERFORMANCE & FOAMING

The fire performance of this product has been measured and documented according to Listings and Approvals stated in this document. The foaming properties depend on equipment used and other variables such as water and ambient temperatures. Average expansion 8:1, average ¼ drainage time 03:00 minutes using UNI 86 test nozzle.

#### 8. SPRINKLER APPLICATION

Sprinkler applications are especially challenging for any foam due to the very low operating pressure and the very low expansion reached. Applying foam through a sprinkler is a very forceful application method and requires foam that can handle direct application and partial submersion into the fuel without losing its fire performance and burnback resistance. Foams that shall be regarded as suitable for sprinkler applications shall also be able to withstand limited time of water deluge directly onto the foam blanket without losing its burnback properties. Viking AFFF 3%S C6 has passed these tests showing very good extinguishing and burnback properties. Refer to the FM Approval Guide and UL Listing for acceptable system configurations used with this concentrate and specific sprinkler SINS and their associated minimum application rates.



## TECHNICAL DATA

## VIKING AFFF 3%S C6 FOAM CONCENTRATE

### 9. STORAGE / SHELF LIFE

Stored in original unbroken packaging the product can have a long shelf life. Shelf life of 20+ years will be found in temperate climates. As with all foams, shelf life will be dependent on storage temperatures and conditions. If the product is frozen during storage or transport, thawing will render the product completely usable.

Synthetic foam concentrates should be stored in stainless steel or plastic containers or bladder tanks which have been approved and listed for long term compatibility with this specific foam. Since electrochemical corrosion can occur at joints between different metals when they are in contact with foam concentrate, only one type of metal should be used for pipelines, fittings, pumps, and tanks employed in the storage of foam concentrates. We recommend following our guidelines for storage and handling ensuring favorable storage conditions.

### 10. SCOPE OF DELIVERY

We supply this product in 25 litre and 6.5 US gallon cans, 200 litre and 55 US gallon drums, 1000 litre and 265 US gallon IBC containers and in bulk on special request.

### 11. INSPECTIONS, TESTS AND MAINTENANCE

The foam concentrate should be tested annually. Refer to respective requirements, according to the relevant standards for Inspection, Testing and Maintenance such as NFPA11 or EN13565-2. If applicable, refer to FM Global Property Loss Prevention Datasheet 4-12 for specific test and commissioning criteria. In addition, the "Authority Having Jurisdiction" (AHJ) may have additional maintenance, testing and inspection requirements that must be followed.

### 12. DISPOSAL



At the end of use the product packaging should be disposed of via the national recycling system. Some IBC Tote containers may be part of a national collection scheme. Details will be attached to the IBC Tote if this service is available. Foam Concentrate should be disposed of according to local regulations.

### 13. AVAILABILITY

Please contact Viking for further information.

The product is available directly from Viking and official distributors only.

**EMEA: Viking SA**, ZI Haneboesch, L-4562 Differdange / Niederkorn, Tel.: +352 58 37 37 - 1, Fax: +352 38 37 36, [vikinglux@viking-emea.com](mailto:vikinglux@viking-emea.com)

**Americas: The Viking Corporation**, 210 N. Industrial Park Drive, Hastings, Michigan 49058, Toll free phone: (800) 968-9501

**APAC: The Viking Corporation (Far East) Pte. Ltd.**, 69 Tuas View Square, Westlink Techpark, Singapore 637621  
Tel: (+65) 6 278 4061, Fax: (+65) 6 278 4609, Email: [vikingsingapore@vikingcorp.com](mailto:vikingsingapore@vikingcorp.com)

### 14. GUARANTEE

For details of warranty, refer to Viking's current list price schedule or contact Viking directly.

### 15. COMPATIBILITY

Contact Viking with questions regarding the compatibility of this product.