





BS Series filter housings use a Facet's stainless steel high efficiency basket strainer. A single pass of product through the system removes solids such as rust, dirt, scale, granules and other particles commonly found in liquid process streams.

Facet BS Series filter housings are available in several standard sizes to accommodate specific flow and filtration requirements. They are designed with no internal moving parts to provide easy service and reduced maintenance costs. Each housing is manufactured using quality materials and workmanship to give long-lasting, dependable service.

These housings are fitted with a cleanable basket made of stainless steel preforated plate with stainless steel mesh.

Standard Design Features

- Body: Welded carbon steel construction, other materials available on request
- ASME Code, Section VIII construction, stamped and certified or "CE" marked
- Designed for 150 psi (10.5 kg/cm²) at 240°F (115°C); higher pressure and temperature ratings available on request
- Head closures: swing bolt closure
- Head gasket: Buna-N O-ring, other materials available on request
- Inlet and outlet permanently marked
- Exterior: Primer coated
- Interior: Epoxy coated
- Headlift furnished on 20" (508 mm) and larger

Standard Connections

Inlet and outlet: 150# RF (ANSI) flanged
Side and bottom drain: 3000# NPT


• Vent and relief valve: ¾" 3000# NPT

• Pressure gauge: ¾" 3000# NPT

Options

- Air eliminator
- Differential pressure gauge
- Pressure relief valve
- · Manual drain valve
- Stainless steel wedge wire basket
- Thru bolts closure

BS Series Basket Strainers



DATA

MODEL NUMBER	øa		b		С		d		е	
	in	mm	in	mm	in	mm	in	mm	in	mm
BS-2	51/2	140	11 ¹³ / ₁₆	300	5½	140	171⁄4	438	9¾	248
BS-3	65/8	168	16 ¹¹ / ₃₂	415	613/16	175	231/4	590	16¾	425
BS-4	85/8	219	26¾	680	9½	241	36	914	20	508
BS-6	10¾	273	4111/32	1050	10½	270	52	1320	22¾	580
BS-8	12¾	324	447/8	1140	13	330	57¾	1467	27	686
BS-10	14	356	511/5	1300	13¾	350	65	1651	281/4	720
BS-12	18	458	491/4	1251	151/4	389	641/2	1638	331/4	845
BS-14	18	458	63	1620	150¾	400	79½	2020	341/4	870
BS-16	20	508	71½	1816	19¾	501	91	2311	36	914
BS-20	24	610	74¾	1899	231/2	598	98½	2502	411/4	1060
BS-24	28	711	1101/4	2800	31½	800	141¾	3600	48	1220

Other sizes available on request.